

Tel: +420-571-751500 Fax: +420-571-751515 Email: info@robe.cz

iFORTE® LTX LightMaster Side/Rear

iFORTE LTX LightMaster is an accessory of externally mounted programmable followspot handles with a control panel and two individual faders that allow you to create a quality follow spot from the iFORTE® LTX WB and iFORTE® LTX FS fixtures.



Available in either sideways or back mounted option, the handles feature two programmable faders (for example for dimmer and iris) and a control panel with touch screen display and four custom programmable jog-wheels and ten assignable buttons for a fully-customizable user experience.

The programmable buttons, jog-wheels and faders allow the operator to comfortably trigger and control dimmer, iris, focus, zoom, frost, colours or other features of the unit. Internal fixture's settings allow you to fully tailor pan/tilt movement behaviour by adjusting tension smoothness and resistance.

While in use by a follow spot operator, the remote desk can still take control of all the internal features of the unit (like dimmer, colours etc.).

Quick mounting in back or side position is assured by using quarter turn lock screws. The control panel connects to the unit via USB connection.



Tel: +420-571-751500 Fax: +420-571-751515 Email: info@robe.cz

Technical Specification

Main features

- Activation & Blackout buttons
- Pan & Tilt freeze buttons
- User setting of controllable attributes
- 4 control jog-wheels
- 2 faders mounted on the handles with direct control of the key features 0-100% (for example dimmer and iris), assignable to any fixture properties (focus, zoom, frost, etc)
- 10 preset buttons with a direct access of the pre-programmed features
- Saving and uploading of custom settings
- Compatible with: iFORTE® LTX, iFORTE® LTX FS

Control and programming


- Display: QVGA Robe touch screen with battery backup
- Movement control: manual

Electrical specification and connections

- Power and data in connector: USB B
- Ethernet port in/out: RJ45

Approvals

- CE Compliant
- cETLus Compliant



ROBE®

Tel: +420-571-751500 Fax: +420-571-751515 Email: info@robe.cz

Mechanical specification

• LightMaster Side:

• Height: 190.8 mm (7.5")

• Width: 680.6 mm (26.8")

• Depth: 295.9 mm (11.7")

• LightMaster Rear:

• Height: 306.3 mm (12.05")

• Width: 736.9 mm (29")

• Depth: 803.1 mm (31.6")

• Weight:

• LightMaster Side: 3.5 kg (7.7 lbs)

• LightMaster Rear: 8.1 kg (17.6 lbs)

• Tripod: 6.5 kg (17.2 lbs)

Adaptor for tripod: 3.6 kg (7.9 lbs)

Fixation option: iFORTE® LTX WB

Included items

• Tripod:

• Min. height 60 cm (23.6")

• Max. height 110 cm (43.3")

Adaptor for tripod: 99018543

Spigot: 12052044

USB-C to USB-B cable: 13053786

Optional accessories

• LightMaster Side:

• Single Top Loader Case: 10120221

• LightMaster Rear:

Single Top Loader Case: 10120344

Legal

- iFORTE® is a Registered Trademark of Robe lighting s. r. o.
- iFORTE® LTX LightMaster Side and iFORTE® LTX LightMaster Rear are patented by Robe lighting s. r. o. and are protected by one or more pending or issued patents